



Reducer Bushing (Hex)

APC Part Number	Male Pipe Thread (NPT)	Female Pipe Thread (NPT)	Overall Diameter	Overall Length
AP1000M-750F	1.000	0.750	1.625	1.800
AP1000M-500F	1.000	0.500	1.625	1.800
AP1000M-375F	1.000	0.375	1.625	1.800
AP1000M-250F	1.000	0.250	1.625	1.800
AP1000M-125F	1.000	0.125	1.625	1.800
AP1000M-062F	1.000	0.062	1.625	1.800
AP0750M-500F	0.750	0.500	1.125	1.430
AP0750M-375F	0.750	0.375	1.125	1.430
AP0750M-250F	0.750	0.250	1.125	1.430
AP0750M-125F	0.750	0.125	1.125	1.430
AP0750M-062F	0.750	0.062	1.125	1.430
AP0500M-375F	0.500	0.375	0.875	1.325
AP0500M-250F	0.500	0.250	0.875	1.325
AP0500M-125F	0.500	0.125	0.875	1.325
AP0500M-062F	0.500	0.062	0.875	1.325
AP0375M-250F	0.375	0.250	0.750	1.565
AP0375M-125F	0.375	0.125	0.750	1.565
AP0375M-062F	0.375	0.062	0.750	1.565
AP0250M-125F	0.250	0.125	0.625	1.260
AP0250M-062F	0.250	0.062	0.625	1.260
AP0125M-062F	0.125	0.062	0.565	1.075



15K Hardware

Maximum Working Pressure = 15,000psi (1034 bar)